



**Features:**

Used in CD-H2545F-XX series Housing  
 Accepta AWG #24~28 wire range  
 Material : Phosphor Bronze  
 Finished : Tin-Plated  
 Qty/reel : 15,000 PCS  
 Thickness: 0.2 mm

**Specification**

Pitch between poles : 2.54mm  
 Rated Voltage : 250V AC, DC  
 Rated Current : 3.0A  
 Withstand voltage : 800V AC/Minute  
 Insulation resistance : 1,000M Ohms/Min  
 Temperature Range : -40°C ~ +105°C



DESCRIPTION(內容):	DRAWN(製圖):	GENERAL TOLERANCE: (公差)	REV:	REV	DESCRIPTION	DATE
			R1			
<b>2.54mm(.100") Pitch Terminal (RoHS)</b>	KAY	.X ±0.25	UNIT:	R0	RELEASE	2011.09.05
	CHECKED(確認):	.XX ±0.15	mm	R1	更換確認章	2020.02.17
PART NO: (料號) CD-T2545M	MANDY	.XXX ±0.05	SIZE:	R2		
DWG NO(圖號): 2545M-T	APPROVAL(核准):	SCALE(比例):	A4	R3		
	JOHNNY	FREE	SHEET: 1/1			