



SPECIFICATION:
 PITCH BETWEEN POLES : 2.5mm
 CURRENT RATING : 3A
 VOLTAGE RATING : 250V
 CONTACT RESISTANCE : INITIAL VALUE/10mΩ max.
 AFTER ENVIRONMENTAL TESTING/20mΩ max.
 INSULATION RESISTANCE : 1000 MΩ (min.)
 WITHSTAND VOLTAGE : 800V AC/MINUTE
 TEMPERATURE RANGE : -25°C TO +85°C
 APPLICABLE WIRE: AWG #22 TO #30
 FEATURES:
 AVAILABLE NUMBER OF CIRCUITS 2 TO 15
 MATERIAL : NYLON 66 UL94V-0

Poles	PART NO.	DIM:(mm)	
		A	B
02	CE-H250-02	2.50	7.00
03	CE-H250-03	5.00	9.50
04	CE-H250-04	7.50	12.00
05	CE-H250-05	10.00	14.50
06	CE-H250-06	12.50	17.00
07	CE-H250-07	15.00	19.50
08	CE-H250-08	17.50	22.00
09	CE-H250-09	20.00	24.50
10	CE-H250-10	22.50	27.00
11	CE-H250-11	25.00	29.50
12	CE-H250-12	27.50	32.00
13	CE-H250-13	30.00	34.50
14	CE-H250-14	32.50	37.00
15	CE-H250-15	35.00	39.50



 承洧科技股份有限公司
 Cherg Wee Technology Corp.

DESCRIPTION(內容):
 EH2.5mm HOUSING(RoHS)
 PART NO:
 (料號) CE-H250-XX
 DWG NO(圖號): 2505-H

DRAWN(製圖):
 GONG
 CHECKED(確認):
 Mandy
 APPROVAL(核准):
 Johnny

GENERAL TOLERANCE:
 (公差)
 .000 ±0.08
 .00 ±0.13
 .0 ±0.25
 SCALE(比例):
 FREE

REV:	REV	DESCRIPTION	DATE
R3	R0	變更環保章字樣	2006.08.17
UNIT: mm	R1	修改接觸阻抗單位	2006.11.18
SIZE: A4	R2	修改圖框	2007.05.21
SHEET: 1/1	R3	2014年料號P數編碼統一兩碼	2014.12.19