



Specifications:

- Material: Nylon 66, UL 94V-0
- Voltage Rating: 250V
- Current Rating: 5A
- Withstand Voltage: 1500V AC/Minute
- Insulation Resistance: $1000M\Omega$ min.
- Temperature Range: $-25^{\circ}C \sim +85^{\circ}C$
- Contact Resistance: Initial value/ $10m\Omega$ max.
After environmental testing/ $20m\Omega$ max.
- Standard Color: Black

Dimensional & Ordering Information:

Circuits	Part No	Dimensions mm	
		A	B
02	CMF-H300M-1x02	3.00	7.0
03	CMF-H300M-1x03	6.00	10.0
04	CMF-H300M-1x04	9.00	13.0
05	CMF-H300M-1x05	12.00	16.0
06	CMF-H300M-1x06	15.00	19.0
07	CMF-H300M-1x07	18.00	22.0
08	CMF-H300M-1x08	21.00	25.2
09	CMF-H300M-1x09	24.00	28.2
10	CMF-H300M-1x10	27.00	31.2
11	CMF-H300M-1x11	30.00	34.2
12	CMF-H300M-1x12	33.00	37.2



DESCRIPTION(內容):
3.0mm (.118") Micro-Fit connector (RoHS)
 PART NO:
 (料號) **CMF-H300M-1×XX**
 DWG NO(圖號): **5750-H-1X**

DRAWN(製圖):
GONG
 CHECKED(確認):
MANDY
 APPROVAL(核准):
JOHNNY

GENERAL TOLERANCE:
 (公差)
 .000 : ± 0.08
 .00 : ± 0.13
 .0 : ± 0.25
 SCALE(比例):
FREE

REV: **R2**
 UNIT: **mm**
 SIZE: **A4**
 SHEET: **1/1**

REV	DESCRIPTION	DATE
R0	RELEASE	2009.05.05
R1	2014年8月料號P數編碼統一兩碼	2015.01.21
R2	更換確認章	2019.09.02
R3		