


P. C. B LAYOUT TOP VIEW



SPECIFICATION
 1. Rating : DC 30V 0.5A;
 2. Contact resistance: $\leq 0.05\Omega$;
 3. Insulation resistance: $\geq 100M\Omega$ (DC250V);
 4. Withstand voltage: 500VAC ;
 5. Insertion and extraction force: 3-30N;
 6. life test: 5,000 cycles.

4	CONTACT FOOT	1	BRONZE	—	Ni-Plating
3	CONTACT FOOT	1	BRONZE	—	Ni-Plating
2	CONTACT FOOT	1	BRONZE	—	Ni-Plating
1	HOUSING	1	PPA	—	—
NO.	DESCRIPTION	QTY	MATERIAL	COLOR	REMARK



DESCRIPTION(內容):
PHONE JACK (RoHS)

PART NO:
 (料號) CPJ-S3013D
 DWG NO(圖號): PJ-S3013D

DRAWN(製圖):
 mandy
 CHECKED(確認):
 MANDY
 APPROVAL(核准):
 JOHNNY

GENERAL TOLERANCE:
 (公差)
 X ±0.50 Angle
 .X ±0.30 X ±3°
 .XX ±0.20 .X ±2°
 .XXX ±0.10 .XX ±1°

SCALE(比例):
 FREE

REV:
R1
 UNIT:
mm
 SIZE:
A4
 SHEET:
1/1

REV	DESCRIPTION	DATE
R0	RELEASE	2014.06.03
R1	圖面更新	2019.08.05
R2		
R3		

A

B

C

D

E