

Specifications:

Material:

- Base: Polyester 94V-0, PBT+30% glass-filled
- Contact: Brass, Gold-Plated
- Voltage Rating: 250V
- Current Rating: 3A
- Withstand Voltage: 1000V AC/Minute
- Insulation Resistance: 1000M Ω min.
- Temperature Range: -25°C~+85°C
- Contact Resistance: Initial value/10m Ω max.
After environmental testing/20m Ω max.



Dimensional & Ordering Information:

Circuits	Part No	Dimensions mm	
		A	B
02	CPU-02	2.54	7.62
03	CPU-03	5.08	10.16
04	CPU-04	7.62	12.70
05	CPU-05	10.16	15.24
06	CPU-06	12.70	17.78
07	CPU-07	15.24	20.32
08	CPU-08	17.78	22.86
09	CPU-09	20.32	25.40
10	CPU-10	22.86	27.94
11	CPU-11	25.40	30.48
12	CPU-12	27.94	33.02



承洧科技股份有限公司
Chong Wei Technology Corp.

DESCRIPTION(內容):
**2.54mm (.100") Pitch
Wire-to-Board Header(RoHS)**

PART NO:
(料 號) CPU-XX
DWG NO(圖號): 2545-RT

DRAWN(製圖):
GONG

CHECKED(確認):

TERESA

APPROVAL(核准):

JOHNNY

GENERAL TOLERANCE:
(公差)

.00 : ± 0.15
.0 : ± 0.25

SCALE(比例):

FREE



REV:
R3

UNIT:
mm

SIZE:
A4

SHEET:
1/1

REV

R0

R1

R2

R3

DESCRIPTION

RELEASE(RoHS) & DIP標示位置更正
修改接觸阻抗單位

2007年圖面版本更新
變更電鍍成份 (Tin→Gold)

補充尺寸(A)

2014年8月料號P數編碼統一兩碼

DATE

2006.07.27
2006.11.18

2007.10.09
2008.05.08

2008.12.26

2016.12.01