



SPECIFICATIONS

Current rating : 2A AC, DC

Voltage rating : 250V AC, DC

Temperature range : -25°C to +85°C

Contact resistance : 20mΩ Max.

Insulation resistance : 1000MΩ Min.

Withstanding voltage : 800V AC/minute

Material : Nylon 66, UL94V-2

Terminal Material : Brass/Tin-Plated



Ordering Information & Dimensions

Poles	Dimension (mm)		Part No.	Note.
	A	B		
02	2.50	5.10	CS-W250R-02	
03	5.00	7.60	CS-W250R-03	
04	7.50	10.10	CS-W250R-04	
05	10.00	12.60	CS-W250R-05	
06	12.50	15.10	CS-W250R-06	
07	15.00	17.60	CS-W250R-07	
08	17.50	20.10	CS-W250R-08	
09	20.00	22.60	CS-W250R-09	
10	22.50	25.10	CS-W250R-10	



承洧科技股份有限公司
Chereng Weei Technology Corp.

DESCRIPTION(內容):
2.5mm Wire-to-Board Header
Dip 90° Type(RoHS)

PART NO:
(料 號) CS-W250R-XX
DWG NO(圖號): 2501-XX-RT

DRAWN(製圖):
GONG
CHECKED(確認):
MANDY
APPROVAL(核准):
JOHNNY

GENERAL TOLERANCE:
(公差)
X.XX ± 0.2
X.X ± 0.3
SCALE(比例):
FREE

REV:
R5
UNIT:
mm
SIZE:
A4
SHEET:
1/1

REV	DESCRIPTION	DATE
R0	RELEASE環保料	2006.07.28
R1	變更環保字樣	2006.10.04
R2	13-20Pin停產	2010.01.21
R3	11-12Pin停產	2011.01.17
R4	2014年8月料號P數編碼統一兩碼	2015.01.27
R5	新增銅材描述	2019.03.20