



RECOMMENDED P.C.BOARD HOLE DIM.

SPECIFICATIONS

Electrical
 Current Rating: 5A
 Voltage Rating: 250V(AC)
 Contact Resistance: 20mΩ max.
 Withstand Voltage: 1000V AC/1min.
 Insulation Resistance: 1000MΩ min.
 Material
 Insulator: Nylon 66, UL94V-2
 Color: Natural
 Contact: Brass 1.14mm(0.45")Square Wire Pins
 Plating: Tin Plated
 Temperature Range: -25°C ~ +85°C

Poles	Dimension		Part NO.
	A	B	
2	5.08	10.22	CW-W508R-02
3	10.16	15.30	CW-W508R-03
4	15.24	20.38	CW-W508R-04
5	20.32	25.46	CW-W508R-05
6	25.40	30.54	CW-W508R-06
7	30.48	35.62	CW-W508R-07
8	35.56	40.70	CW-W508R-08
9	40.64	45.78	CW-W508R-09
10	45.72	50.86	CW-W508R-10



DESCRIPTION(內容): 5.08mm Wire-to-Board Header DIP 90° Type (RoHS)	DRAWN(製圖): GONG	GENERAL TOLERANCE: (公差) X.XX ± 0.3 X.X ± 0.5	REV: R4	REV	DESCRIPTION	DATE		
	CHECKED(確認): MANDY		UNIT: mm	R1		變更環保章字樣	2006.09.06	
	PART NO: (料號) CW-W508R-XX	APPROVAL(核准):	SCALE(比例): FREE	SIZE: A4		R2	可量產Pin數:2-10, 不再量產:12Pin.	2009.03.17
	DWG NO(圖號): 5081-XX-RT	JOHNNY		SHEET: 1/1		R3	2014年Pin數料號編碼統一	2014.09.17
				R4	更換確認章	2019.09.02		