



Series	Connector Type	Contact Plating	Material	Pin Length	mm	Number of Contacts
F303	X	X	X	-	DXXX	-XX
(Female Header Single Row) F303 (2.00 H:4.6 W:2.4)	S: Straight Type	G: Gold Flash T: Tin Plated A: 10U" Gold B: 15U" Gold C: 20U" Gold	P: PBT C: LCP N: Nylon-6T N1: Nylon-9T (Standard: N)	S-D D030 (Standard: S-D024)		(02 TO 40 Contacts)

© Duplex Plating  
D: Gold Flash/Tin  
(Standard: G)



<b>DESCRIPTION(内容):</b> 2.0mm Female Header H:4.6 W:2.4 180° (RoHS)	<b>DRAWN(製圖):</b> 邓文广	<b>GENERAL TOLERANCE:(公差):</b> .X .XXX .XX .X° .XXX .XX°	<b>REV: A/1</b> <b>UNIT: mm</b> <b>SIZE: A4</b> <b>SHEET: 1/1</b>	<b>REV</b> 1 2 3 4	<b>DESCRIPTION</b> △此符號表示重點管控尺寸	<b>DATE</b> 2019.11.13	
	<b>CHECKED(確認):</b> 邓文广	<b>APPROVAL(核准):</b> Jimmy	<b>SCALE(比例):</b> 1:XX				
	<b>PART NO:(料號):</b> F303-SG_-D030-XX						
	<b>DWG NO(圖號):</b>						