



### Specifications

Current Rating	:0.8 Amp
Insulator Resistance	:900 Megohms Min.
Contact Resistance	:20 m ohms max.
Dielectric Withstanding	:AC 500 V
Operating Temperature	:-40°C ~ +105°C
Soldering Temperature	:260°C for 3~5sec Max.
Contact Material	:Phosphor Bronze
Insulator Material	:High Temperature Thermoplastic. UL 94V-0
Standard	:LCP
Finish	:Gold Plated
Standard	:Gold Flash all over



Series	Connector Type	Contact Plating	Material	Pin Length mm	Number of Contacts	Other
F703	X	X	X	DXXX	-XX	-XT
(Female Header Dual Row) F703(1.00 H:2.00 W:1.5)	M:SMT Type	G:Gold Flash T:Tin Plated A:10U"Gold B:15U"Gold C:20U"Gold ©Duplex Plating D:Gold Flash/Tin (Standard:G)	C:LCP (Standard:C)	S-D D029	(03 TO 40 Contacts)	AT:A TYPE BT:B TYPE



DESCRIPTION(内容):  
1.0mm Female Header SMT H:2.0  
W:1.5 LCP(RoHS)

PART NO:  
(料 號) F703-MGC-D029-XX-XT

DWG NO(圖號):

DRAWN(製圖):  
黃炳秋

CHECKED(確認):  
黃炳秋

APPROVAL(核准):  
鄧文廣

GENERAL TOLERANCE:  
(公差)

X.	±0.30	X.°	±5.0°
.X	±0.20	.X°	±3.0°
.XX	±0.15	.XX°	±1.0°

SCALE(比例):  
XX:XX



REV:  
A/2

UNIT:  
mm

SIZE:  
A4

SHEET:  
X/X

REV

1

2

3

4

DESCRIPTION

△ 此符號表示重點管控尺寸

增加可生产Pin数

DATE

2014.12.11

2015.09.02