



Note:
 1. Material
 1.1: Housing: LCP UL94-V0; Color:Natural
 1.2: Actuator: LCP UL94-V0; Color:Black
 1.3: Contact: Phosphor Bronze.
 1.4: LEG: Phosphor Bronze.
 2. Plating
 2.1: Contact: TIN 100U" MIN OVERALL NICKEL 50U" MIN .
 2.2: LEG: TIN 100U" MIN OVERALL NICKEL 50U" MIN.

PART NO:
 FPC220F1 XX - CT X
 T:Tube Packing
 R:Tape Reel Packing
 04~32PIN



Number of Contacts	Dimension			
	A	B	C	D
04	8.70	3.00	6.60	5.15
05	9.70	4.00	7.60	6.15
06	10.70	5.00	8.60	7.15
07	11.70	6.00	9.60	8.15
08	12.70	7.00	10.60	9.15
09	13.70	8.00	11.60	10.15
10	14.70	9.00	12.60	11.15
11	15.70	10.00	13.60	12.15
12	16.70	11.00	14.60	13.15
13	17.70	12.00	15.60	14.15
14	18.70	13.00	16.60	15.15
15	19.70	14.00	17.60	16.15
16	20.70	15.00	18.60	17.15
17	21.70	16.00	19.60	18.15
18	22.70	17.00	20.60	19.15
19	23.70	18.00	21.60	20.15
20	24.70	19.00	22.60	21.15
21	25.70	20.00	23.60	22.15
22	26.70	21.00	24.60	23.15
23	27.70	22.00	25.60	24.15
24	28.70	23.00	26.60	25.15
25	29.70	24.00	27.60	26.15
26	30.70	25.00	28.60	27.15
27	31.70	26.00	29.60	28.15
28	32.70	27.00	30.60	29.15
29	33.70	28.00	31.60	30.15
30	34.70	29.00	32.60	31.15
31	35.70	30.00	33.60	32.15
32	36.70	31.00	34.60	33.15

FPC/FFC Insert Direction
 Recommended P.C.B Layout

Recommended FPC Dimension



DESCRIPTION(內容):
1.0mm Pitch Easy On FPC/FFC H:2.0 前掀蓋式 Lower Contact Connector (RoHS)
 PART NO:
 (料號) **FPC220F1XX-CTX**
 DWG NO(圖號): **FPC1019-xxRL-TAx**

DRAWN(製圖):
Shih
 CHECKED(確認):
MANDY
 APPROVAL(核准):
JOHNNY

GENERAL TOLERANCE:
 (公差) .X ±0.30
 .XX ±0.20
 .XXX ±0.10
 X* ±5*
 .X* ±2*
 SCALE(比例):
FREE

REV: **R1**
 UNIT: **mm**
 SIZE: **A4**
 SHEET: **1/1**

REV	DESCRIPTION	DATE
R0	RELEASE	2013.10.18
R1	更換確認章	2019.09.12
R2		
R3		