



SPECIFICATION:

- **Poles: 4~30**
- **Voltage rating:**
AC, DC, 200V(50HZ)
AC, DC, 50V(200HZ)
- **Current rating:**
0.4A, AC/DC
- **Withstand voltage:**
200V AC/minutes
- **Working Temperature:**
-25°C~ +85°C
- **Insulation resistance:** >500MΩ
- **Contact resistance:** <0.02Ω
- **Terminal material:**
Phosphor Bronze/Tin-Plated
- **Housing material:**
PA9T UL94V-0 ,Color: Black

| NO. of Contacts (n) | Dimensions | | |
|---------------------|------------|-------|------|
| | A | B | C |
| 04 | 3.0 | 5.10 | 7.0 |
| 05 | 4.0 | 6.10 | 8.0 |
| 06 | 5.0 | 7.10 | 9.0 |
| 07 | 6.0 | 8.10 | 10.0 |
| 08 | 7.0 | 9.10 | 11.0 |
| 09 | 8.0 | 10.10 | 12.0 |
| 10 | 9.0 | 11.10 | 13.0 |
| 11 | 10.0 | 12.10 | 14.0 |
| 12 | 11.0 | 13.10 | 15.0 |
| 13 | 12.0 | 14.10 | 16.0 |
| 14 | 13.0 | 15.10 | 17.0 |
| 15 | 14.0 | 16.10 | 18.0 |
| 16 | 15.0 | 17.10 | 19.0 |
| 17 | 16.0 | 18.10 | 20.0 |
| 18 | 17.0 | 19.10 | 21.0 |
| 19 | 18.0 | 20.10 | 22.0 |
| 20 | 19.0 | 21.10 | 23.0 |
| 21 | 20.0 | 22.10 | 24.0 |
| 22 | 21.0 | 23.10 | 25.0 |
| 23 | 22.0 | 24.10 | 26.0 |
| 24 | 23.0 | 25.10 | 27.0 |
| 25 | 24.0 | 26.10 | 28.0 |
| 26 | 25.0 | 27.10 | 29.0 |
| 27 | 26.0 | 28.10 | 30.0 |
| 28 | 27.0 | 29.10 | 31.0 |
| 29 | 28.0 | 30.10 | 32.0 |
| 30 | 29.0 | 31.10 | 33.0 |

Part No:
FPC228N3 XX - N1T X
 T: Tube Packing
 R: Tape/Reel Packing
 04~30 PIN



承洧科技股份有限公司
Cherg Weei Technology Corp.

DESCRIPTION(內容):
 FPC 1.0mm H:2.8 NON-ZIF SMD
 90° Dual Contact Type(軟排 t:0.3)
 (RoHS)

PART NO:
 (料號) FPC228N3XX-N1TX

DWG NO(圖號): K810DL-SR-XX-PT-X

DRAWN(製圖):
 GONG

CHECKED(確認):
 TERESA

APPROVAL(核准):
 JOHNNY

GENERAL TOLERANCE:(公差)

| | |
|------|-------|
| 0.0 | ±0.35 |
| 0.00 | ±0.20 |

SCALE(比例):
 FREE

REV:
 R1

UNIT:
 mm

SIZE:
 A4

SHEET:
 1/1

| REV | DESCRIPTION | DATE |
|-----|-------------|------------|
| R0 | RELEASE | 2013.10.22 |
| R1 | 圖面更新 | 2019.01.02 |
| R2 | | |
| R3 | | |