



SPECIFICATIONS

Current rating : 2A AC, DC
 Voltage rating : 250V AC, DC
 Temperature range : -25° C to +85 ° C
 Contact resistance : 20mΩ Max.
 Insulation resistance : 1000MΩ Min.
 Withstanding voltage : 800V AC/minute
 Material : Nylon 66, UL94V-0



Ordering Information & Dimensions

Poles	Dimension (mm)		Part No.	Note.
	A	B		
2x02	2.00	5.90	PHD-H20-2x02	
2x03	4.00	7.90	PHD-H20-2x03	
2x04	6.00	9.90	PHD-H20-2x04	
2x05	8.00	11.90	PHD-H20-2x05	
2x06	10.00	13.90	PHD-H20-2x06	
2x07	12.00	15.90	PHD-H20-2x07	
2x08	14.00	17.90	PHD-H20-2x08	
2x09	16.00	19.90	PHD-H20-2x09	
2x10	18.00	21.90	PHD-H20-2x10	
2x11	20.00	23.90	PHD-H20-2x11	
2x12	22.00	25.90	PHD-H20-2x12	
2x13	24.00	27.90	PHD-H20-2x13	
2x14	26.00	29.90	PHD-H20-2x14	
2x15	28.00	31.90	PHD-H20-2x15	
2x16	30.00	33.90	PHD-H20-2x16	



承洧科技股份有限公司
 Cherg Wee Technology Corp.

DESCRIPTION(內容):
 2.0mm Wire-to-Board Housing
 (RoHS)

PART NO:
 (料號) PHD-H20-2xXX
 DWG NO(圖號): 2000D-2xXX

DRAWN(製圖):
 GONG
 CHECKED(確認):
 MANDY
 APPROVAL(核准):
 JOHNNY

GENERAL TOLERANCE:
 (公差)
 X.XX ± 0.2
 X.X ± 0.3
 SCALE(比例):
 FREE

REV:
R4
 UNIT:
 mm
 SIZE:
 A4
 SHEET:
 1/1

REV
R0
R1
R2
R3
R4

DESCRIPTION
 RELEASE
 導入RoHS
 變更環保章字樣
 新增2x2PIN尺寸
 2014年料號修改/統一P數編碼

DATE
2006.03.20
2006.06.29
2006.08.21
2010.07.07
2014.09.11