



P.C.B LAYOUT
TOP VIEW ±0.05

MATERIALS

HOUSING: LCP (UL 94V-0), COLOR: BLACK
 SHELL: COPPER ALLOY, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED

SPECIFICATION

CURRENT RATING: 1.8 AMP MAX (ONLY PIN 1,5), OTHER 1 AMP MAX
 DIELECTRIC WITHSTANDING: 100V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 100M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -25°C~+85°C



DESCRIPTION(內容): MICRO USB AB TYPE, SMT, PCB MOUNT, METAL SHIELD, FEMALE, WITH POST (RoHS) PART NO: (料號) UMMCF-051MGCB2-CF1066 DWG NO(圖號): 22UBH-051-120L	DRAWN(製圖): GONG	GENERAL TOLERANCE: (公差) .X ±0.30 .XX ±0.20	REV: R3	REV	DESCRIPTION	DATE
	CHECKED(確認): TERESA		UNIT: mm	R0		RELEASE
	APPROVAL(核准): JOHNNY	SCALE(比例): FREE	SIZE: A4	R1	修正接地片位置	2013.01.21
			SHEET: 1/1	R2	新增(A)尺寸	2016.05.09
			R3	變更CONTACT RESISTANCE數值(原:50m OHMS MAX)	2016.08.01	