



Specifications

Current Rating : 3 Amps
 Insulator Resistance : 5000 Megohms Min.
 Contact Resistance : 20 m ohms max.
 Dielectric Withstanding : AC 1000 V
 Operating Temperature : $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
 Contact Material : Phosphor Bronze
 Insulator Material : Polyester, UL 94V-0
 Standard : P. B. T
 Finish: Tin, Gold or Duplex Plated
 Standard: Gold Flash all over
 Note:
 Duplex plating: Gold Plated on contact area,
 Tin on solder area

| | | | | | | | |
|---|--|---------------|----------------------------------|---------------|-----|-------------|------|
| 凱帛企業有限公司 KABO ENTERPRISE CO., LTD. | DESCRIPTION(內容) | DRAWN(製圖) | GENERAL TOLERANCE: (公差) | REV: A/2 | REV | DESCRIPTION | DATE |
| | 2.54mm Female Header H:8.50 W:5.00 180° | CHECKED(確認): | .X .XXXX .XX .X° .XXX .XX° | UNIT: mm | 1 | | |
| | PART NO: (料號) Female header-2.54-2020-xx01N | APPROVAL(核准): | SCALE(比例): 1:XX | SIZE: A4 | 2 | | |
| | DWG NO(圖號): | | | SHEET: 1/1 | 3 | | |
| | | | | 4 | | | |