



SPECIFICATIONS

Electrical

Current Rating: 1A AC, DC

Voltage Rating: 50V AC/ max.

Operating Temp.: -25°C ~ +85°C

Insulation Resistance: 100MΩ/ min.

Dielectric Withstanding Voltage: 500V AC/ min.

Contact Resistance: 20mΩ/ max.

Material

Material: PBT, UL94V-0

Poles	Dimension mm (in.)				Part No.
	A	B	C	D	
2	1.0	5.0	2.37	3.00	LH-SH100-02
3	2.0	6.0	3.37	4.00	LH-SH100-03
4	3.0	7.0	4.37	5.00	LH-SH100-04
5	4.0	8.0	5.37	6.00	LH-SH100-05
6	5.0	9.0	6.37	7.00	LH-SH100-06
7	6.0	10.0	7.37	8.00	LH-SH100-07
8	7.0	11.0	8.37	9.00	LH-SH100-08
9	8.0	12.0	9.37	10.00	LH-SH100-09
10	9.0	13.0	10.37	11.00	LH-SH100-10
11	10.0	14.0	11.37	12.00	LH-SH100-11
12	11.0	15.0	12.37	13.00	LH-SH100-12
13	12.0	16.0	13.37	14.00	JH-SH100-13
14	13.0	17.0	14.37	15.00	JH-SH100-14
15	14.0	18.0	15.37	16.00	JH-SH100-15
16	15.0	19.0	16.37	17.00	JH-SH100-16
20	19.0	23.0	20.37	21.00	JH-SH100-20

B尺寸公差如下:

2P~10P±0.10mm

11P~20P±0.20mm

		公差/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE		單位/Unit mm	品名(Title):		 鍊亨電子有限公司 LAI HENG TECHNOLOGY LTD. TEL:(02) 8228-6487 FAX:(02) 8228-6486
		.XX ±0.1 .X ±0.25		比例/Scale Free	1.0mm Wire-to-Board Housing		
A0	NEW DRAWING	2018.08.09		Size A4	料號/Part No:	圖號/Drawing No:	核准/APPD Joe
REV	概述/REVISION	日期/DATE			LH-SH100-XX	1000-XX	製圖/DR. Mandy
							張數/Sheet 1 of 1
							REV. A0