



SPECIFICATIONS

Current rating : 2A AC,DC
 Voltage rating : 250V AC,DC
 Temperature range : -25°C to +85 °C
 Contact resistance : 20mΩ Max.
 Insulation resistance : 1000MΩ Min.
 Withstanding voltage : 800V AC/minute
 Material : Nylon 66, UL94V-0

Ordering Information & Dimensions

Poles	Dimension (mm)		Part No.
	A	B	
2x02	2.0	5.9	LH-PHD200-2x02
2x03	4.0	7.9	LH-PHD200-2x03
2x04	6.0	9.9	LH-PHD200-2x04
2x05	8.0	11.9	LH-PHD200-2x05
2x06	10.0	13.9	LH-PHD200-2x06
2x07	12.0	15.9	LH-PHD200-2x07
2x08	14.0	17.9	LH-PHD200-2x08
2x09	16.0	19.9	LH-PHD200-2x09
2x10	18.0	21.9	LH-PHD200-2x10
2x11	20.0	23.9	LH-PHD200-2x11
2x12	22.0	25.9	LH-PHD200-2x12
2x13	24.0	27.9	LH-PHD200-2x13
2x14	26.0	29.9	LH-PHD200-2x14
2x15	28.0	31.9	LH-PHD200-2x15
2x16	30.0	33.9	LH-PHD200-2x16
2x17	32.0	35.9	LH-PHD200-2x17
2x20	38.0	41.90	LH-PHD200-2x20

PART NO.:
LH-PHD 200 - 2xXX

_____ No.of Poles: 2x02~2x120
 _____ Pitch:2.00mm
 _____ Housing Series No.

			公差/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	單位/Unit mm	品名(Title) : 2.0mm Wire-to-Board Housing Dual Row	鍊亨電子有限公司 LAI HENG TECHNOLOGY LTD. TEL:(02) 8228-6487 FAX:(02) 8228-6486	
A0	NEW DRAWING	2018.08.16	X.XX ±0.25 X.X ±0.35	比例/Scale Free	料號/Part No : LH-PHD200-2×XX		圖號/Drawing No : 2000D-2×XX
REV	概述/REVISION	日期/DATE		Size A4			核對/APPD. Joe 審核/CHKD. Joe 製圖/DR. Mandy 張數/Sheet 1 of 1 REV. A0