



SPECIFICATIONS

Electrical

- Current Rating: 5A AC, DC
- Voltage Rating: 250V AC, DC
- Operating Temp.: -25°C ~ +85°C
- Insulation Resistance: 1000mΩ/ min.
- Dielectric Withstanding Voltage: 1500V AC/ min.
- Contact Resistance: 10mΩ/ max.

Material

Material: Nylon66, UL94V-2

Poles	Dimension mm (in.)		Part No.
	A	B	
2	3.96	8.45	LH-MX396-02
3	7.92	12.39	LH-MX396-03
4	11.88	16.35	LH-MX396-04
5	15.84	20.31	LH-MX396-05
6	19.80	24.27	LH-MX396-06
7	23.76	28.23	LH-MX396-07
8	27.72	32.19	LH-MX396-08
9	31.68	36.15	LH-MX396-09
10	35.64	40.11	LH-MX396-10
11	39.60	44.07	LH-MX396-11
12	43.56	48.03	LH-MX396-12
13	47.52	51.99	LH-MX396-13
14	51.48	55.95	LH-MX396-14
15	55.44	59.91	LH-MX396-15
16	59.40	63.87	LH-MX396-16
17	63.36	67.83	LH-MX396-17
18	67.32	71.79	LH-MX396-18
20	75.24	79.71	LH-MX396-20

PART NO.:
LH-MX 396 - XX

└── No.of Poles: 02~20
 └── Pitch:3.96mm
 └── Housing Series No.

			公差/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	單位/Unit mm	品名(Title):	3.96mm Wire-to-Board Housing			鍊亨電子有限公司 LAIHENG TECHNOLOGY LTD. TEL:(02) 8228-6487 FAX:(02) 8228-6486
			X.XX ±0.35 X.X ±0.5	比例/Scale Free	料號/Part No.:				
A0	NEW DRAWING	2018.08.16		Size A4	圖號/Drawing No.:	3960-XX			核對/APPD. Joe
REV	概述/REVISION	日期/DATE							製圖/DR. Mandy
									張數/Sheet 1 of 1
									REV. A0