



P.C.B LAYOUT

**Technical Data:**

Material:

Insulator body (housing): PBT, UL94-V0, Color-Black.  
 Pin (outsleeve): Brass, machined, CuZn38pb2.  
 Tin plated: 80u" nickel, 100~150u" Tin Plated.  
 Clip (4 finger): Beryllium copper.  
 Gold plated: 80u" nickel/full Gold-flashed.

Electrical:

Current rating: 3 Amps / contact max.  
 Insulation resistance: > 1000 MΩ at V=100V.  
 Operating: 60 Veff.

Mechanical:

Operating temperature: Gold plated: -55°C to +125°C.  
 Tin plated: -40°C to +105°C.  
 Soldering temperature: +200°C 10s max.

**Part No.**  
**LICS 254 R 04 022**

No. of Contacts:  
 XX:06~32  
 04:0.4 Inch(10.16 mm) Wide

R:Round Pin  
 (Machined pin)

Pitch:2.54mm

Series No:IC Socket

			公差/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
A0	NEW DRAWING	2018.08.16	
REV	概述/REVISION	日期/DATE	

單位/Unit mm	品名/Title :
比例/Scale	IC SOCKET 2.54mm Round Pin 0.4 Inch Wide 22P
Free	
Size A4	料號/Part No : LICS254R04022
	圖號/Drawing No : ISM22T1/04

**鍊亨電子有限公司**  
 LAI HENG TECHNOLOGY LTD.  
 TEL:(02) 8228-6487 FAX:(02) 8228-6486

核加/APPD. 740 審核/CHKD. Joe 製圖/DR. Mandy 張數/Sheet 1 of 1 REV. A0