



SPECIFICATION

Current Rating: 1 A
 Withstanding Voltage: 500V AC
 Insulation Resistance: 1000 Megohms Min.
 Operating Temperature: -55°C to +105°C

MATERIAL

Contact: Copper Alloy
 Insulator: NYLON 6T, UL94V-0
 Plating: All Gold or Tin



ORDER INFORMATION

LP/H 127 S X N a A c A b - 2xXX
 Pitch: 1.27mm Type S: 180° Material N: NYLON 6T No. Of Contact Dual Row: 2x02~2x50

Contact Plating

- T : Tin
- G : Gold Flash
- G3 : All Gold 3u"
- G5 : All Gold 5u"
- G10: All Gold 10u"
- G15: All Gold 15u"
- G20: All Gold 20u"
- G30: All Gold 30u"

a: Pin Chart Dimension See Pin Chart
 A: Insulation Height: 1.0mm, Width: 3.4mm
 c: Pin Chart Dimension See Pin Chart
 A: Insulation Height: 1.0mm, Width: 3.4mm
 b: Pin Chart Dimension See Pin Chart

Standard: 3A0A2.3

Pin Chart:

a : _____ mm


Standard: 3.0mm

b : _____ mm

Standard: 2.3mm

c : _____ mm

Standard: 0.0mm



Recommended P.C.Board
 Hold Layout

公認/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE			單位/Unit mm	品名/Title : 1.27mm Pin Header H:1.0 W:3.4 Dual Row Dual Base Straight Dip Type	鍊亨電子有限公司 LAI HENG TECHNOLOGY LTD. TEL:(02) 8228-6487 FAX:(02) 8228-6486
A0	NEW DRAWING	2018.08.16	比例/Scale Free	料號/Part No : LP/H127SXNaAcAb-2×XX	
REV	概述/REVISION	日期/DATE	Size A4	核加/APPD. Joe	審核/CHKD. Joe
				製圖/DR. Mandy	張數/Sheet 1 of 1
					REV. A0