



Recommended P.C.Board Hold Layout

SPECIFICATION

Current Rating: 1 A
 Withstanding Voltage: 500V AC
 Insulation Resistance: 1000 Megohms Min.
 Operating Temperature: -55°C to +105°C (NYLON 6T)

MATERIAL

Contact: Copper Alloy
 Insulator: Polyester, UL94V-0
 NYLON 6T
 Plating: All Gold or Tin

ORDER INFORMATION

LP/H 200 U X N a / c B b - 2xXX

Pitch: 2.0mm Type U: 90° Up Angle

Material N: NYLON 6T

No. Of Contact Dual Row: 2x02~2x40

a: Pin Chart Dimension See Pin Chart
 c: Pin Chart Dimension See Pin Chart
 B: Insulation Height: 1.5mm, Width: 4.0mm
 b: Pin Chart Dimension See Pin Chart

Standard: 4/1B2.8

Contact Plating

- T : Tin
- G : Gold Flash
- G3 : All Gold 3u"
- G5 : All Gold 5u"
- G10 : All Gold 10u"
- G15 : All Gold 15u"
- G20 : All Gold 20u"
- G30 : All Gold 30u"

Pin Chart:

a : _____ mm

Standard: 4.0mm

b : _____ mm

Standard: 2.8mm

c : _____ mm

Standard: 1.0mm

公認/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE			單位/Unit mm	品名/Title : 2.0mm Pin Header H:1.5 W:4.0 Dual Row Up Angle Dip Type	銻亨電子有限公司 LAI HENG TECHNOLOGY LTD. TEL:(02) 8228-6487 FAX:(02) 8228-6486
A0	NEW DRAWING	2018.08.16	比例/Scale Free	料號/Part No : LP/H200UXNa/cBb-2×XX	
REV	概述/REVISION	日期/DATE	Size A4	圖號/Drawing No : 200-GR2-2×XX-ABC-N(H1.5)	核准/APPD. Joe 審核/CHKD. Joe 製圖/DR. Mandy 張數/Sheet 1 of 1 REV. A0