

SPECIFICATION

Contact Current Rating: 3 Amperes
 Contact resistance: 20 mΩ Max
 Insulation Resistance: 1000 MΩ Min.
 Operating Temperature: -40°C to +105°C
 Dielectric Withstanding Voltage: 600V AC RMS 60 SECONDS

MATERIAL

Insulator: PBT, UL94V-0
 Contact: Brass
 Plating: All Gold or Tin


LP/H 254 R X P a A c / b - 3xXX
 Pitch:2.54mm Type R:90° Material P: PBT
 No.Of Contact Three Row: 3x03~3x40

a: Pin Chart Dimension See Pin Chart
 A: Insulation Height:2.54mm, Width:2.54mm
 c: Pin Chart Dimension See Pin Chart
 b: Pin Chart Dimension See Pin Chart

Standard: 6A1.5/3

Pin Chart:

a : _____ mm
 Standard:6.0mm
 b : _____ mm
 Standard:3.0mm
 c : _____ mm
 Standard:1.5mm



P.C.B Hole Layout

公認/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE			單位/Unit mm	品名/Title : 2.54mm Pin Header H:2.5 W:7.5 Three Row Down Angle Type	<p>LAI HENG TECHNOLOGY LTD. TEL:(02) 8228-6487 FAX:(02) 8228-6486</p>
A0	NEW DRAWING	2018.06.14	比例/Scale Free Size A4	料號/Part No : LP/H254RXP aAc/b-3×XX	
REV	概述/REVISION	日期/DATE		圖號/Drawing No :	核加/APPD. 740 審核/CHKD. Joe 製圖/DR. Mandy 張數/Sheet 1 of 1 REV. A0