



SPECIFICATIONS

Electrical
 Voltage Rating: 100V AC, DC
 Current Rating: 2A AC, DC
 Withstand Voltage: 800V AC/ min
 Insulation Resistance: 1000MΩ/ min
 Temperature Range: -40°C ~ +85°C

Material
 Wafer: High Temperature Plastic Nylon 6T UL94V-0
 Pin: High Strength Brass With Tin Over Nickel Plated
 Applicable PC Board Thickness: 0.8 ~ 1.6mm
 Contact Resistance: Initial Value / 10mΩ max.
 After environmental testing 20mΩ max.

PART NO.	A	B	C
LW-PH200R-02-S	2.00	7.90	4.80
LW-PH200R-03-S	4.00	9.90	6.80
LW-PH200R-04-S	6.00	11.90	8.80
LW-PH200R-05-S	8.00	13.90	10.80
LW-PH200R-06-S	10.00	15.90	12.80
LW-PH200R-07-S	12.00	17.90	14.80
LW-PH200R-08-S	14.00	19.90	16.80
LW-PH200R-09-S	16.00	21.90	18.80
LW-PH200R-10-S	18.00	23.90	20.80
LW-PH200R-11-S	20.00	25.90	22.80
LW-PH200R-12-S	22.00	27.90	24.80
LW-PH200R-13-S	24.00	29.90	26.80
LW-PH200R-14-S	26.00	31.90	28.80
LW-PH200R-15-S	28.00	33.90	30.80
LW-PH200R-16-S	30.00	35.90	32.80

公差/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE		單位/Unit mm	品名(Title):
X.XX ±0.25		比例/Scale Free	2.0mm Wire-to-Board Header SMT 90° SM3 Type
X.X ±0.35		Size A4	料號/Part No: LW-PH200R-XX-S
A0 NEW DRAWING	2018.08.16		圖號/Drawing No: 2001S-XX-RT
REV 概述/REVISION	日期/DATE		

鍊亨電子有限公司
 LAI HENG TECHNOLOGY LTD.
 TEL: (02) 8228-6487 FAX: (02) 8228-6486

核對/APPD. Joe 審核/CHKD. Joe 製圖/DR. Mandy 報數/Sheet 1 of 1

REV. A0