



Cable ID: P8-069-5 [5]

Date / Time: 01/05/2016 09:00:31 AM

Headroom 2.7 dB (NEXT 36-45)

Test Limit: ISO Patch Cord Cat6A 1.0m

Cable Type: Cat 6A F/UTP

Calibration Date: 03/25/2015

Operator: Your Name

Software Version: 2.7700

Limits Version: 1.9400

NVP: 74.0%

Test Summary: PASS

Model: DTX-1800

Main S/N: 8943015

Remote S/N: 8943016

Main Adapter: DTX-PC6A/MN ISO/IEC

Remote Adapter: DTX-PC6A/SR ISO/IEC


Length (ft)	[Pair 12]	4
Prop. Delay (ns)	[Pair 36]	6
Delay Skew (ns)	[Pair 36]	1
Resistance (ohms)	[Pair 12]	0.0



4 ft



Wire Map (T568B) PASS



	Worst Case Margin		Worst Case Value	
PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45		45-78	
NEXT (dB)	2.7		3.4	
Freq. (MHz)	339.0		490.0	
Limit (dB)	35.6		31.2	

PASS	MAIN	SR	MAIN	SR
Worst Pair	36		36	
RL (dB)	2.1		2.1	
Freq. (MHz)	381.0		381.0	
Limit (dB)	11.3		11.3	

