

# 2.54mm Female Header

## Specifications

- ❑ 型態: 180度、90度、SMT
- ❑ 電鍍方式: 鍍金、鍍霧錫、鍍亮錫、鍍錫鉛...(鍍層厚度依客戶要求作調整)
- ❑ 排數: 單排、雙排
- ❑ Pin數: 1x2~1x40 Pin、2x2~2x40 Pin
- ❑ 塑膠材質: PBT、NY6T (UL 94-V0)
- ❑ 塑膠高度: 5.0、7.1、8.5mm
- ❑ Terminal: Straight、Right Angle、SMT Type
- ❑ Plating: Gold、Matte Tin、Bright Tin、Lead Tin...(The plating model and plating thickness are adjustable as the customer's request)
- ❑ Row of pin: Single row、Dual rows
- ❑ Positions: 1x5~1x50 Pin、2x5~2x50 Pin
- ❑ Plastic Material: NY9T、LCP (UL 94-V0)
- ❑ Plastic height: 5.0、7.1、8.5mm

## Order information

**2 5 4 0 2 X 0 X X X X X X X**

(1) (2) (3) (4) (5) (6) (7) (8) (9)

- (1) Pitch: 254=2.54mm
- (2) Series: 02=Female Header
- (3) Terminal: **S**=Straight Type  
**R**=Right Angle Type / **M**=SMT Type
- (4) 0=Female
- (6) No. Of Positions: 002 to 080
- (7) Plastic Type: A, B, C,...
- (8) Row of Pin: 1=Single Row, 2=Dual Rows
- (9) Terminal Dia. Type: 01, 02, 03...

## (5)Plating Options:

Full Gold Type	Selective Plated Type(Tin=100μ")	Full Tin(Matting Tin, Bright Tin00")
G:Gold Flash	J:Gold Flash	
E:Gold 1μ"	I:Gold 1μ"	
A:Gold 3μ"	K:Gold 3μ"	
B:Gold 5μ"	L:Gold 5μ"	
C:Gold 10μ"	M:Gold 10μ"	
D:Gold 15μ"	N:Gold 15μ"	
E:Gold 30μ"	P:Gold 30μ"	

## Drawing

