




1.27mm Pitch Pin Header Dual Row Single Body Straight DIP TYPE (Dual Row: 1.27*1.27mm)



Specification:

Insulator Material:	High Temperature Thermoplastic, UL94V-0.
Contact Material:	Copper Alloy, 0.40x0.40mm.
Contact Plating:	Au or Sn over Nickel.
Current Rating:	1 AMP.
Insulator Resistance:	500 Megohms Min.
Dielectric Withstanding:	500V AC for 1 Minute.
Operating Temperature:	-40°C ~ +105°C.
Max. Processing Temp.:	230°C for 30~60 seconds. 260°C for 10 seconds.

RoHS Compliant



Ordering Information: E19 - XXX - XX - XX - XXX

1
2
3
4
5

1 --> Series Number:	E19		
2 --> Contact Positions:	2~100Pin: 002~100,		
3 --> Dim. "H" option:	10: H=1.00,	11: H=1.60,	12: H=2.50,
4 --> Dim. "B & C" option:	10: B=1.65, C=2.29,	11: B=1.91, C=2.29,	12: B=2.70, C=2.29, 13: B=3.05, C=2.29,
	As request: B/C=XX/XX, For Eg: B=2.05, C=2.60, Code=2.05/2.60,		
5 --> Plating option:	100: Full Gold Flash Plated	500: Tin Plated	600: Selective Gold Flash Plated
	610: 10U" selective Gold plated	615: 15U" selective Gold plated	
	620: 20U" selective Gold plated	630: 30U" selective Gold plated	