

636

D-Sub Coaxial Connectors

Ordering Information:

	636-	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Series No.											
No. of Pins											
A:2W2 B:3W3 K: 1W1 P: 21W1											
C:5W1 D:5W5 L: 9W4 Q: 25W3											
E:7W2 F:8W8 M: 13W6 R: 27W2											
G:11W1 H:13W3 N: 17W2 S: 24W7											
I:21W4 J:36W4 O: 17W5 T: 43W2											
	U: 47W1										
Connector Type											
1:Male											
2:Female											
3:Only Housing Male											
4:Only Housing Female											
Contact Tail Style:											
1:Solder Type											
2:Straight Dip Type											
Pin Type											
21:Power Pin Current Rating 10A											
22:Power Pin Current Rating 20A											
24:Power Pin Current Rating 40A											
17:Signal Coaxial Pin Impedance:75 Ohms											
00:W/O Coaxial Pin & Power Pin											
Plated On Coaxial Pin											
1:3U"gold											
2:15U"gold											
3:30U"gold											
Plated On Signal Pin											
0:Gold flash											
1:3U"gold											
2:15U"gold											
3:30U"gold											
Plated On Shell											
1:Front shell Ni plating and rear shell Tin plating											
Position On Insulator											
1:Black											
2:Green											
Option Of Clinch Nut											
0:Standard through hole ☐ 3.05mm											
1:Riveted with UNC 4-40 thread insert 4.0mm Top shell											
2:Riveted with UNC 4-40 thread insert 4.0mm Bottom shell											
3:Riveted with UNC 4-40 thread insert 5.8mm Top shell											
4:Riveted with UNC 4-40 thread insert 5.8mm Bottom shell											
5:Riveted with UNC 4-40 thread insert 7.0mm Boardhook											
Hexagonal Bolt Option											
0:Loose hexagonal bolts											
1:Assembled hexagonal bolts											