



Specifications

Current Rating : 1 Amp
 Insulator Resistance : 1000 Megohms Min.
 Contact Resistance : 20 m ohms max.
 Dielectric Withstanding : AC 500 V
 Operating Temperature : -40°C ~ +105°C
 Soldering Temperature : 260°C for 3~5sec Max.
 Contact Material : Phosphor Bronze
 Standard : Gold Flash all over
 Insulator Material : Polyester, UL 94V-0
 Standard : Nylon-6T (Black)

ORDER INFORMATION

JPCB 127 C S X X 2.4 - 1xXX
 Pitch: 1.27mm
 Insulation Height: 4.6mm
 Width: 2.5mm
 TYPE S: 180°
 Contactn Plating
 T : Tin
 G : Gold Flash
 G2 : Gold 2u"
 DIP: 2.4mm
 No. Of Contact
 Single Row: 1x02~1x40
 Material
 N: NYLON 6T
 C: LCP



P.C.B Layout

		公認/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE		品名(Title):	
		X. ±0.5	X° ±3°	1.27*1.27mm Female Header H:4.6 W:2.5 180° Single Row	
		.XX ±0.2	.XX° ±1°	料號/Part No:	
A0	NEW DRAWING	2015.08.23	.XXX ±0.1	圖號/Drawing No:	
REV	概述/REVISION	日期/DATE		JPCB127CSX X 2.4-1xXX MF127EV1XX-1XX-X	
核准/APPD	審核/CHKD.	製圖/DR.	比例/Scale	Size	張數/Sheet
David	Joe	Mandy	Free	A4	1 of 1
				單位/Unit	REV.
				mm	A0